


# Sprinter P6V1700 data sheet



Terminal:



## Specifications:

Exide type designation	Part number	Nom. Voltage V	Nominal capacity C <sub>10</sub> 1.80Vpc 25°C Ah	Power 15min 1.60 Vpc 25°C W	Length l max. mm	Width b/w max. mm	Height h1 max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Max. perm current 5 secs. A	Terminal
P6V1700	NAPW061700HP0MC	6	122	1700	272.0	166.0	190.0	25.00	2.3	2930	1700	M-M8

Part numbers not valid for North America, use type for ordering!

## Constant-current discharge in A (@ 25 °C):

Part number	Exide type designation	VpC	3min	5min	10min	15min	20min	30min	45min	1h	2h	3h	5h	8h	10h	20h
NAPW061700HP0MC	P6V1700	1.95	179.0	176.0	165.0	145.0	130.0	103.0	77.4	62.9	33.8	24.1	15.5	10.6	9.0	4.8
NAPW061700HP0MC	P6V1700	1.90	286.0	267.0	223.0	187.0	162.0	125.0	94.0	76.1	41.4	29.2	19.1	12.7	10.9	5.8
NAPW061700HP0MC	P6V1700	1.85	388.0	349.0	279.0	227.0	192.0	145.0	107.0	83.4	46.3	32.5	21.3	13.8	11.6	6.2
NAPW061700HP0MC	P6V1700	1.80	479.0	421.0	319.0	254.0	209.0	155.0	114.0	89.4	49.3	34.3	22.8	14.7	12.2	6.5
NAPW061700HP0MC	P6V1700	1.75	562.0	483.0	353.0	275.0	223.0	163.0	117.6	92.4	51.4	35.3	23.5	15.2	12.5	6.6
NAPW061700HP0MC	P6V1700	1.70	629.0	529.0	377.0	291.0	234.0	168.5	120.8	94.5	53.3	36.5	24.2	15.4	12.6	6.7
NAPW061700HP0MC	P6V1700	1.65	676.0	563.0	395.0	299.0	241.0	173.6	123.8	96.5	54.6	37.8	24.3	15.5	12.6	6.7
NAPW061700HP0MC	P6V1700	1.60	698.0	582.0	406.0	308.0	247.0	177.6	126.9	98.5	55.4	38.4	24.4	15.5	12.6	6.7

## Constant-power discharge in W/block (@ 25 °C):

Part number	Exide type designation	VpC	3min	5min	10min	15min	20min	30min	45min	1h	2h	3h	5h	8h	10h
NAPW061700HP0MC	P6V1700	1.90	1640	1537	1267	1067	919.8	711.0	545.6	445.4	246.6	174.6	114.7	76.1	62.9
NAPW061700HP0MC	P6V1700	1.85	2176	1982	1586	1302	1107	848.3	632.1	498.4	279.1	193.9	126.9	82.2	68.0
NAPW061700HP0MC	P6V1700	1.80	2634	2349	1808	1454	1212	906.2	664.2	523.5	290.3	203.0	136.0	88.3	72.6
NAPW061700HP0MC	P6V1700	1.75	3020	2654	1982	1566	1282	950.0	689.3	541.1	300.3	211.1	140.1	89.3	73.6
NAPW061700HP0MC	P6V1700	1.70	3346	2876	2092	1628	1330	977.4	699.8	552.7	311.6	218.2	142.1	90.3	74.1
NAPW061700HP0MC	P6V1700	1.65	3520	3007	2161	1663	1358	994.1	713.0	560.7	316.7	222.3	143.1	91.4	74.1
NAPW061700HP0MC	P6V1700	1.60	3596	3063	2210	1700	1379	1002	720.3	567.7	319.7	224.3	143.1	91.4	74.1