

AC/DC[®] Transformers

www.acdc.com.tr



Isolation Transformers 3 Phase Input - 3 Phase Output



75 - 400 kVA

- Isolation Class : B,F or H
- Star, Delta, Zig-Zag and required angle of phase
- Laked Under Vacuum
- Dried in oven
- Construction Specification: Open type or protected type
- Plate or Ferrit Nuve
- 2 years warranty
- 10 years space part warranty

TÜV
AUSTRIA
HELLAS
EN ISO 9001:2008

CE, ISO 9001

Your Positive Energy source ...

MODEL	Tr3U-0753	Tr3U-1003	Tr3U-1603	Tr3U-2003	Tr3U-2503	Tr3U-4003
Power	75 kVA	100 kVA	160 kVA	200 kVA	250 kVA	400 kVA
The Feature of Transformer	Isolation Transformer					
Type	Dry Type					
Brand	AC/DC					
Isolation Class	Class B (120 °C), Class F (155 °C) or Class H (180 °C)					
Place of Use	Indoor , Outdoor (Optional)					
With Box / Without Box	Without Box, With Box (Optional)					
Colling	Naturel Air (AN) or Forced Air (AF)					
Protection Class	IP20, IP23 (Optional), IP54 (Optional)					
Connections Group	YY, DY or another connect groups					
Primer Voltage	400 VAC					
Primer Frequency	50 / 60 Hz.					
Primer Current	114 A	150 A	240 A	300 A	375 A	600 A
Seconder Voltage	400 VAC					
Seconder Frequency	50 / 60 Hz.					
Seconder Current	108 A	144 A	230 A	288 A	360 A	576 A
Endurance Voltage	3 kV RMS (1 Minute)					
Connection	As per to customer requirements: All types of terminals and lugs					
Colour	RAL 7032 (Can be changed upon request)					
Dimensions (W x H x L) (cm)	85x90x70	100x110x75	120x120x75	120x120x75	120x120x75	150x150x80
Weight (kg)	420 kg	600 kg	700 kg	800 kg	900 kg	1500 kg
Warranty	2 Year					
TRANSFORMER LIFETIME	10 YEARS					

*** AC/DC reserves the right to make any changes to data without prior notice.

Update: 06 / 08 / 2012

